

DRILL PIPE PERFORMANCE CHARACTERISTICS SHEET

DRILL PIPE	
Pipe Size and Weight:	3.5" x 13.3PPf
Pipe Grade:	S
Range:	2
Tool Joint:	4-3/4" x 2.563" DPHT38
PE	
Dimensional Data	New
OD (in)	3.500
Wall thickness (in)	0.368
Minimum wall (%)	95.0
ID (in)	2.764
Cross sectional area pipe body (in ²)	3.621
Cross sectional area OD (in ²)	9.621
Cross sectional area ID (in ²)	6.000
Section modulus (in ³)	2.572
Polar section modulus (in ³)	5.144
erformance Data	New
Torsional strength (ft-lbs)	33,393
Tensile strength (lbs)	488,825
80% Torsional strength (ft-lbs)	26,714
Burst Pressure capacity (psi)	24,840
Collapse capacity (psi)	25,400
TOOL JOINT (Minimum yield strength: 120 KSI)	
Dimensional Data	New
OD (in)	4.750
ID (in)	2.563
Pin tong length (in)	10
Box tong length (in)	15.5
Connection	DPHT38
Performance Data	New
Torsional Strength (ft-lbs)	26,833
Max Recommended Make-up Torque (ft-lbs)	16,100
Min Recommended Make-up Torque (ft-lbs)	12,075
Tensile strength (lbs)	649,200
Tool joint/Drill pipe torsional ratio (New pipe)	0.80
	0.00
Drill pipe assembly with DPHT38 tool joint	
Average length (ft)	31.5
Drift size (in)	2.438

Note: Tool Joint and Pipe body values were derived as per API RP 7G and DS1 Latest edition. The above values are for refrence only. DPI LLC is not responsible or liable for any loss or damage or injury resulting from the use of above information.