

DRILL PIPE PERFORMANCE CHARACTERISTICS SHEET

DRILL PIPE		
Pipe Size and Weight:	3.5" x 13.3PPf	
Pipe Grade:	S	្រឹស្ត 2
Range:	2	
Tool Joint:	5" x 2.125" NC38	- $ $ $ $ $+$ $ $ $+$
PIPE		 \ -
Dimensional Data	New	
OD (in)	3.500	
Wall thickness (in)	0.368	
Minimum wall (%)	95.0	─
ID (in)	2.764	─
Cross sectional area pipe body (in²)	3.621	
Cross sectional area OD (in²)	9.621	-
Cross sectional area ID (in²)	6.000	
Section modulus (in³)	2.572	─
Polar section modulus (in³)	5.144	
	5	
Performance Data	New	
Torsional strength (ft-lbs)	33,393	
Tensile strength (lbs)	488,825	─
80% Torsional strength (ft-lbs)	26,714	─ <u> </u> !
Burst Pressure capacity (psi)	24,840	
Collapse capacity (psi)	25,404	¼ ¦
		─
TOOL JOINT (Minimum yield strength: 120 KSI)		
Dimensional Data	New	2.764" ID
OD (in)	5.000	
ID (in)	2.125	
Pin tong length (in)	10	
Box tong length (in)	12.5	
Connection	NC38	
Performance Data	New	
Torsional Strength (ft-lbs)	26,515	
Max Recommended Make-up Torque (ft-lbs)	15,909	
Min Recommended Make-up Torque (ft-lbs)	11,932	2.125" ID
Tensile strength (lbs)	842,440	
Tool joint/Drill pipe torsional ratio (New pipe)	0.79	\rightarrow \rightarrow \leftarrow \leftarrow
		<u> </u>
Drill pipe assembly with NC38 tool joint		
Average length (ft)	31.5	
Drift size (in)	2.000	→
		\ ! /
		\ \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\

Note: Tool Joint and Pipe body values were derived as per API RP 7G and DS1 Latest edition. The above values are for refrence only. DPI LLC is not responsible or liable for any loss or damage or injury resulting from the use of above information. All data described are the users own risk & responsibility.