

DRILL PIPE PERFORMANCE CHARACTERISTICS SHEET

Pipe Size and Weight:	4.5" x 16.6PPf
Pipe Grade:	X
Range:	2
Tool Joint:	
PE	
mensional Data	New
OD (in)	4.500
Wall thickness (in)	0.337
Minimum wall (%)	95.0
ID (in)	3.826
Cross sectional area pipe body (in ²)	4.407
Cross sectional area OD (in ²)	15.904
Cross sectional area ID (in²)	11.497
Section modulus (in ³)	4.271
Polar section modulus (in ³)	8.543
Performance Data	New
Torsional strength (ft-lbs)	39,022
Tensile strength (lbs)	418,707
80% Torsional strength (ft-lbs)	31,218
Burst Pressure capacity (psi)	12,450
Collapse capacity (psi)	12,763
OOL JOINT	
Dimensional Data	New
OD (in)	6.250
ID (in)	3.250
Pin tong length (in)	9
Box tong length (in)	12
Connection	DPDS46
Performance Data	New
Torsional Strength (ft-lbs)	43,333
Max Recommended Make-up Torque (ft-lbs)	26,000
Min Recommended Make-up Torque (ft-lbs)	19,500
Tensile strength (lbs)	901,200
Tool joint/Drill pipe torsional ratio (New pipe)	1.11
	1.1.1
Drill pipe assembly with DPDS46 tool joint	
Average length (ft)	31.5
Drift size (in)	3.125

Note: Tool Joint and Pipe body values were derived as per API RP 7G and DS1 Latest edition. The above values are for refrence only. DPI LLC is not responsible or liable for any loss or damage or injury resulting from the use of above information.