

DRILL PIPE PERFORMANCE CHARACTERISTICS SHEET

DRILL PIPE	
Pipe Size and Weight:	5-1/2" x 21.9 PPf
Pipe Grade:	G
Range:	2
Tool Joint:	7.25" x 3.5" 5-1/2FH
PIPE	
Dimensional Data	New
OD (in)	5.500
Wall thickness (in)	0.361
Minimum wall (%)	95.0
ID (in)	4.778
Cross sectional area pipe body (in ²)	5.828
Cross sectional area OD (in ²)	23.758
Cross sectional area ID (in ²)	17.930
Section modulus (in ³)	7.031
Polar section modulus (in ³)	14.062
erformance Data	New
Torsional strength (ft-lbs)	70,994
Tensile strength (lbs)	611,963
80% Torsional strength (ft-lbs)	56,795
Burst Pressure capacity (psi)	12,061
Collapse capacity (psi)	10,753
TOOL JOINT	
Dimensional Data	New
OD (in)	7.250
ID (in)	3.500
Pin tong length (in)	10
Box tong length (in)	12
Connection	5-1/2FH
Performance Data	New
Torsional Strength (ft-lbs)	72,483
Max Recommended Make-up Torque (ft-lbs)	43,490
Min Recommended Make-up Torque (ft-lbs)	32,618
Tensile strength (lbs)	1,619,231
Tool joint/Drill pipe torsional ratio (New pipe)	1.02
Drill pipe assembly with 5-1/2FH tool joint	24 5
Average length (ft)	31.5
Drift size (in)	3.375

Note: Tool Joint and Pipe body values were derived as per API RP 7G and DS1 Latest edition. The above values are for refrence only. DPI LLC is not responsible or liable for any loss or damage or injury resulting from the use of above information. All data described are the users own risk & responsibility.