

## DRILL PIPE PERFORMANCE CHARACTERISTICS SHEET

Pipe Size and Weight:	5-1/2" x 21.9 PPf	<u> </u>	₹ <del>                                    </del>
Pipe Size and Weight: Pipe Grade:	5-1/2 X 21.9 PPT S		
Range:	2		\ !
Tool Joint:	7.00" x 4.00" DPDS55	_   ,	
1001 John.	7.00 X 4.00 DI D000		_ /   -
IPE		$\dashv$	1
Dimensional Data	New		17!
OD (in)	5.500		1/:
Wall thickness (in)	0.361		- 1/ i
Minimum wall (%)	95.0		
ID (in)	4.778		
Cross sectional area pipe body (in²)	5.828		
Cross sectional area OD (in²)	23.758		
Cross sectional area ID (in²)	17.930		
Section modulus (in³)	7.031		
Polar section modulus (in³)	14.062		
Performance Data	New		
Torsional strength (ft-lbs)	91,278		
Tensile strength (lbs)	786,809		
80% Torsional strength (ft-lbs)	73,023		
Burst Pressure capacity (psi)	15,507	31.5	
Collapse capacity (psi)	12,674	—   'n	
, , , , , , , , , , , , , , , , , , ,	,		
OOL JOINT			
Dimensional Data	New	_	<del>  ←                                 </del>
OD (in)	7.000		
ID (in)	4.000		
Pin tong length (in)	10		
Box tong length (in)	12		
Connection	DPDS55	$\dashv$	
Performance Data	New	-	
Torsional Strength (ft-lbs)	74,167		
Max Recommended Make-up Torque (ft-lbs)	44,500		
Min Recommended Make-up Torque (ft-lbs)	33,375		
Tensile strength (lbs)	1,292,500		\
Tool joint/Drill pipe torsional ratio (New pipe)	0.81		<b>/</b>
100. joint Drin pipe torsionar ratio (New pipe)	0.01	<b>- </b>   7	不(   ;>
		_	<b> </b>   <b> </b>
Orill pipe assembly with DPDS55 tool joint			
Average length (ft)	31.5	<u> </u>	<u>₩</u> ᠳ ⊨
		<u> </u>	ιlμ
Drift size (in)	3.875		Λ .

Note: Tool Joint and Pipe body values were derived as per API RP 7G and DS1 Latest edition. The above values are for refrence only. DPI LLC is not responsible or liable for any loss or damage or injury resulting from the use of above information. All data described are the users own risk & responsibility.