

DRILL PIPE PERFORMANCE CHARACTERISTICS SHEET

DRILL PIPE			
Pipe Size and Weight:	5-1/2" x 24.7 PPf		$\overline{}$
Pipe Size and Weight: Pipe Grade:	G 5-1/2 X 24.7 PP1		[2]
Range:	G 	 	· \
Tool Joint:	7.00" x 4.0" 5-1/2FH	 	
1001 Joint.	7.00 X 4.0 3-1/2FH		
PIPE		-)
Dimensional Data	New		
OD (in)	5.500		
Wall thickness (in)	0.415		
Minimum wall (%)	95.0		
ID (in)	4.67		
Cross sectional area pipe body (in²)	6.630		
Cross sectional area OD (in²)	23.758		
Cross sectional area ID (in²)	17.129		
Section modulus (in³)	7.844		
Polar section modulus (in³)	15.688		
		_	
Performance Data	New	_	
Torsional strength (ft-lbs)	79,204	_	
Tensile strength (lbs)	696,111	_	
80% Torsional strength (ft-lbs)	63,363		
Burst Pressure capacity (psi)	13,865	31.5	
Collapse capacity (psi)	14,013	_	
TOOL JOINT		- 	
Dimensional Data	New		
OD (in)	7.000		
ID (in)	4.000		
Pin tong length (in)	10		
Box tong length (in)	12		
Connection	5-1/2FH		
Barfarra Bata	N	_	
Performance Data Torsional Strength (ft-lbs)	New 55,933		
Max Recommended Make-up Torque (ft-lbs)	33,560	-	
Min Recommended Make-up Torque (ft-lbs)	25,170		
Tensile strength (lbs)	1,265,802	- 	
Tool joint/Drill pipe torsional ratio (New pipe)	0.71		_ /
	J., 1		T
		<u> </u>	10"
Drill pipe assembly with 5-1/2FH tool joint			=
Average length (ft)	31.5		
Drift size (in)	3.875		\
			/
•			,

Note: Tool Joint and Pipe body values were derived as per API RP 7G and DS1 Latest edition. The above values are for refrence only. DPI LLC is not responsible or liable for any loss or damage or injury resulting from the use of above information.