

DRILL PIPE PERFORMANCE CHARACTERISTICS SHEET

DRILL PIPE		
DRIEE PIFE		┦
Pipe Size and Weight:	5-1/2" x 24.7 PPf	
Pipe Grade:	G	7,001,00
Range:	2	
Tool Joint:	7.00" x 3.5" DPDS55	<u> </u>
		
PIPE		─
Dimensional Data	New	
OD (in)	5.500	
Wall thickness (in)	0.415	
Minimum wall (%)	95.0	_
ID (in)	4.67	_
Cross sectional area pipe body (in²)	6.630	_
Cross sectional area OD (in²)	23.758	⊣
Cross sectional area ID (in²)	17.129	_
Section modulus (in³)	7.844	_
Polar section modulus (in³)	15.688	_
Performance Data	New	_
Torsional strength (ft-lbs)	79,204	⊣
Tensile strength (lbs)	696,111	_
80% Torsional strength (ft-lbs)	63,363	
Burst Pressure capacity (psi)	13,865	
Collapse capacity (psi)	14,013	
TOOL JOINT (Minimum Yield strength 120 KSI)		-
Dimensional Data	New	4.67" ID
OD (in)	7.000	
ID (in)	3.500	-1
Pin tong length (in)	10]
Box tong length (in)	12	_
Connection	DPDS55	
		_
Performance Data	New	_
Torsional Strength (ft-lbs)	89,500	_
Max Recommended Make-up Torque (ft-lbs)	53,700	_
Min Recommended Make-up Torque (ft-lbs)	40,275	3.50" ID
Tensile strength (lbs)	1,648,700	_
Tool joint/Drill pipe torsional ratio (New pipe)	1.13	一
		-
Drill pipe assembly with DPDS55 tool joint		
Average length (ft)	31.5	$ \downarrow$ \downarrow \downarrow \downarrow \downarrow
Drift size (in)	3.375	─
Drift Size (III)	3.313	⊣ \ ¦ /
		\ \
:		<u> </u>

Note: Tool Joint and Pipe body values were derived as per API RP 7G and DS1 Latest edition. The above values are for refrence only. DPI LLC is not responsible or liable for any loss or damage or injury resulting from the use of above information.