

DRILL PIPE PERFORMANCE CHARACTERISTICS SHEET

DRILL PIPE			
Diag Olas and Weight	5.7/0" · · · · · · · · · · · · · · · · · · ·	_	→
Pipe Size and Weight:	5-7/8" x 23.4 PPf		<u>2</u>
Pipe Grade: Range:	S 	- '	7.00" (
Tool Joint:	7.00" x 4.0" DPHT55	_	
Tool Joint.	7.00 X 4.0 DFH155	_ .	<u> </u>
PIPE		 	\ <u>\</u>
Dimensional Data	New		
OD (in)	5.875		4.00" ID
Wall thickness (in)	0.361		
Minimum wall (%)	95.0		
ID (in)	5.153		
Cross sectional area pipe body (in²)	6.254		
Cross sectional area OD (in²)	27.109		
Cross sectional area ID (in²)	20.855		
Section modulus (in³)	8.125		
Polar section modulus (in³)	16.251		
			5-7/8"C
Performance Data	New		
Torsional strength (ft-lbs)	105,489		i
Tensile strength (lbs)	844,224		
80% Torsional strength (ft-lbs)	84,391	F-	
Burst Pressure capacity (psi)	14,517	31.5	
Collapse capacity (psi)	10,820	m	
		_	!
FOOL JOINT			5.153" ID
Dimensional Data	New		
OD (in)	7.000		
ID (in)	4.000		!
Pin tong length (in)	10	_	
Box tong length (in)	15	_	
Connection	DPHT55	-	
Performance Data	New		
Torsional Strength (ft-lbs)	77,167		
Max Recommended Make-up Torque (ft-lbs)	46,300		
Min Recommended Make-up Torque (ft-lbs)	34,725		4.00" ID
Tensile strength (lbs)	1,265,800		
Tool joint/Drill pipe torsional ratio (New pipe)	0.73		
		_	
Drill pipe assembly with DPHT55 tool joint			
Average length (ft)	31.5		<u> </u>
Drift size (in)	3.875		\
Make & Break: 3 Cycles			\
			<u> </u>
•			

Note: Tool Joint and Pipe body values were derived as per API RP 7G and DS1 Latest edition. The above values are for refrence only. DPI LLC is not responsible or liable for any loss or damage or injury resulting from the use of above information.