

DRILL PIPE PERFORMANCE CHARACTERISTICS SHEET

DRILL PIPE	
Ding Size and Waight	6 E/0" y 25 2 DDf
Pipe Size and Weight: Pipe Grade:	6-5/8" x 25.2 PPf S
Pipe Grade: Range:	2
Tool Joint:	
	0.U X 3 0-3/0FH
PIPE	
Dimensional Data	New
OD (in)	6.625
Wall thickness (in)	0.33
Minimum wall (%)	95.0
ID (in)	5.965
Cross sectional area pipe body (in ²)	6.526
Cross sectional area OD (in ²)	34.472
Cross sectional area ID (in ²)	27.945
Section modulus (in ³)	9.786
Polar section modulus (in ³)	19.572
erformance Data	New
Torsional strength (ft-lbs)	127,045
Tensile strength (lbs)	881,035
80% Torsional strength (ft-lbs)	101,636
Burst Pressure capacity (psi)	11,768
Collapse capacity (psi)	6,036
TOOL JOINT (120 KSI minimum yield strength)	
Dimensional Data	New
OD (in)	8.000
ID (in)	5.000
Pin tong length (in)	10
Box tong length (in)	13
Connection	6-5/8FH
Performance Data	New
Torsional Strength (ft-lbs)	73,660
Max Recommended Make-up Torque (ft-lbs)	44,196
Min Recommended Make-up Torque (ft-lbs)	33,147
Tensile strength (lbs)	1,448,416
Tool joint/Drill pipe torsional ratio (New pipe)	0.58
Drill pipe assembly with 6-5/8FH tool joint	
Average length (ft)	31.5
Drift size (in)	4.875
•	
·	

Note: Tool Joint and Pipe body values were derived as per API RP 7G and DS1 Latest edition. The above values are for refrence only. DPI LLC is not responsible or liable for any loss or damage or injury resulting from the use of above information. All data described are the users own risk & responsibility.