

## DRILL PIPE PERFORMANCE CHARACTERISTICS SHEET

DRILL PIPE		1
DIVILLE I II L		
Pipe Size and Weight:	6-5/8" x 27.7 PPf	
Pipe Grade:	S	(8.500" OD
Range:	2	-     \ \ <del>  6.500</del> OD
Tool Joint:	8.5" x 5" 6-5/8FH	
PIPE		
Dimensional Data	New	
OD (in)	6.625	j   5" ID
Wall thickness (in)	0.362	_
Minimum wall (%)	95.0	_
ID (in)	5.901	_
Cross sectional area pipe body (in²)	7.123	_
Cross sectional area OD (in²)	34.472	_
Cross sectional area ID (in²)	27.349	-
Section modulus (in³)	10.578	<b>-                                     </b>
Polar section modulus (in³)	21.156	_
Performance Data	New	<b>⊣</b>
Torsional strength (ft-lbs)	137,331	-
Tensile strength (lbs)	961,556	-
80% Torsional strength (ft-lbs)	109,865	_   أ   أ
Burst Pressure capacity (psi) Collapse capacity (psi)	12,909 7,809	
Collapse capacity (psi)	7,809	-
TOOL JOINT (120 KSI minimum yield strength)		<del> </del>
Dimensional Data	New	
OD (in)	8.500	<b> </b>
ID (in)	5.000	7
Pin tong length (in)	10	<b>─</b>
Box tong length (in)	13	
Connection	6-5/8FH	
		_
Performance Data	New	_
Torsional Strength (ft-lbs)	73,667	_
Max Recommended Make-up Torque (ft-lbs)	44,200	_
Min Recommended Make-up Torque (ft-lbs)	33,150	
Tensile strength (lbs)	1,448,416	_
Tool joint/Drill pipe torsional ratio (New pipe)	0.54	
		<b>-                                     </b>
Drill pipe assembly with 6-5/8FH tool joint		<del> </del>
Average length (ft)	31.5	<b>⊣</b> <u>↓ ↓ ↓                               </u>
Average length (It)  Drift size (in)	4.875	┨
Drift Size (III)	4.070	┥ \      /
		\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\

Note: Tool Joint and Pipe body values were derived as per API RP 7G and DS1 Latest edition. The above values are for refrence only. DPI LLC is not responsible or liable for any loss or damage or injury resulting from the use of above information. All data described are the users own risk & responsibility.